

KEY FEATURES

Rugged and waterproof

Long-life battery

806 MHz processor

Integrated GSM WWAN capability

Built-in GPS, bar code scanner and camera options

Integrated Bluetooth, 802.11g wireless capability

Full VGA display

Windows Mobile 6

Small and lightweight



EVERYTHING YOU WANTED IN AN OUTDOOR RUGGED HANDHELD COMPUTER—BUILT IN.

The Trimble® Nomad™ packs even more functionality into one of the most powerful and full-featured rugged handheld computers available. Start with an 806 MHz processor, up to 2 GB of Flash storage, a long-life battery and integrated wireless capabilities like GPS, 802.11g, WWAN and Bluetooth¹. Then select an optional integrated laser bar code scanner and color digital camera. The Nomad handheld also features a high-resolution, sunlight-visible VGA display that shows graphics and maps in crisp detail. And it's fully rugged which means the Nomad handheld computer offers a lower Total Cost of Ownership (TCO) than consumer-grade handhelds².

Built-in versatility

The Nomad computer makes it easy to collect, save and transmit data in the field because it's available with so many built-in capabilities. Compute your location with the integrated GPS receiver for navigation applications. Quickly track your assets with the integrated 1D laser bar code scanner and upload changes from the field. Or capture color images with the 2 megapixel digital camera for inspection, maintenance and repair applications. All models provide a Secure Digital (SDIO) slot to add even more capabilities. Plus, some models offer a CompactFlash (CF) slot or a second USB host as well.

Tough as the outdoors

Like other Trimble rugged handhelds, the Nomad computer meets rigorous MIL-STD-810F military standards for drops, vibration, humidity, altitude and extreme temperatures. It also comes with an IP67 rating. That means the Nomad handheld is completely sealed against dust, and it can survive immersion in up to a meter of water for 30 minutes. Trimble rugged handhelds have proven their reliability in the field with thousands of real-world users.

Fast, powerful and easy to use

Every Nomad handheld comes with an 806 MHz Marvell PXA320 XScale processor, 128 MB RAM and a hot-swappable Lithium Ion (Li-Ion) battery that can work all day without a recharge. The Nomad computer also includes the latest Windows Mobile® 6 software, so it runs all the applications you use most, including a wide range of third-party software for industry-specific applications.

Want to do more outside? Get the handheld that has more inside. Get your hands on a Nomad handheld.

¹ Nomad 800B models have Bluetooth only.
² E-mail us at handhelds@trimble.com for a copy of the TCO White Paper.

Trimble Nomad handheld computer

STANDARD FEATURES

- Windows Mobile 6 (Professional in WWAN models; Classic in all other models)
- Marvell 806 MHz XScale processor
- 128 MB DDR SDRAM
- 512 MB to 2 GB non-volatile Flash storage
- Full VGA display, sunlight-readable color TFT
- Touchscreen
- Rugged submersible design
- Integrated speaker and microphone
- Integrated Bluetooth 2.0
- Secure Digital (SDIO) slot
- Notification LEDs
- USB host and client
- Audio jack
- 15-hour battery life with active use (default settings)
- Keypad backlighting for night use
- 12-month limited warranty

CONFIGURATION OPTIONS

- Integrated Quad-band GSM GPRS/EDGE capability
- Integrated GPS (SiRFStar III, WAAS Capable)
- Integrated 802.11b/g wireless capability
- CompactFlash (CF) (Type II) slot (on 800B, 800L and 800X models only)
- 9-pin RS-232 serial connector
- PDA or numeric style keypad
- Integrated laser 1D bar code scanner
- Integrated digital camera (color, 2 megapixel resolution)
- Second USB host (on 800LD model only)

STANDARD SOFTWARE

- Microsoft Office Mobile
 - Word Mobile
 - Excel Mobile
 - PowerPoint Mobile
 - Outlook Mobile
- Internet Explorer Mobile
- Notes/Tasks
- Calculator
- Windows Media Player
- Microsoft Pictures and Videos
- Online help
- Contacts/Calendar

STANDARD ACCESSORIES

- Rechargeable Li-Ion battery module
- Rugged stylus with spring-loaded tip
- Stylus lanyard
- AC charger
- USB data cable
- User guide
- Hand strap
- Screen protectors
- Getting Started CD with ActiveSync

OPTIONAL ACCESSORIES

- Carry case
- Deluxe case with belt clip & neck strap
- 9-pin serial boot or USB boot
- Serial interface cable
- AA battery module
- Spare battery charger
- Extended CF-Cap
- Tripod bracket
- Range pole bracket
- 12 V vehicle charging cable
- Vehicle mount
- Trigger pistol grip

PHYSICAL

Size 6.92 in x 3.92 in x 1.96 in (17.6 cm x 10 cm x 5.0 cm)
 Weight 21 ounces (596 g) including rechargeable battery

ENVIRONMENT

Operating Temperature. -22 °F to 140 °F (-30 °C to 60 °C)
 MIL-STD 810F, Method 501.4, Procedure II
 (High Temp Operating, +65 °C)
 MIL-STD 810F, Method 502.4, Procedure I, II, III
 (Low Temp Op/Manipulation -35 °C)
 Storage Temperature. -40 °F to 158 °F (-40 °C to 70 °C)
 MIL-STD 810F, Method 501.4, Procedure I
 (High Temp Storage, +70 °C)
 MIL-STD 810F, Method 502.4, Procedure I, II, III
 (Low Temp Storage -40 °C)
 Temperature shock. MIL-STD-810F, Method 503.4, Procedure I (-35 °C/+65 °C)
 Humidity. MIL-STD-810F, Method 507.4
 (Humidity, 90%RH temp cycle -20 °C/+60 °C)
 Water IP67, MIL-STD-810F, Method 512.4, Procedure I,
 Water Jet 12.5 mm dia. @ 2.5-3 m, 100 Liter/min.
 Drop MIL-STD-810F, Method 516.5, Procedure IV 26 drops from 4 ft (1.22 m)
 onto concrete, 6 additional drops at -22 °F (-30 °C),
 6 additional drops at 140 °F (60 °C)
 Sand & dust IP67, MIL-STD-810F, Method 510.3, Procedures I&II, IEC-529 IP-X6
 Vibration. MIL-STD 810F, Method 514.5, Procedure I (Vibration, General
 Minimum Integrity, figure 17) MIL-STD 810F, Method 514.5,
 Procedure II (Vibration, Loose Cargo, figure 5)
 Altitude. MIL-STD-810F, Method 500.4, Procedures I, II & III,
 15,000 ft at 73 °F (23 °C)

ELECTRICAL

Processor. Marvell PXA320 XScale 806 MHz
 Memory. 128 MB DDR SDRAM ~ 30 MB reserved
 Storage Onboard non-volatile NAND Flash 512 MB TO 2 GB ~ 50 MB reserved
 Expansion 1x SDIO slot (all models), 2nd USB host (800LD),
 1x Type II CF slot (800B, 800L, 800X)
 Display. 480 x 640 pixel (VGA) 16 bit color TFT with LED backlight
 Batteries 5200 mAh Li-Ion rechargeable pack*
 I/O USB Host and client, power, audio jack
 Radios Bluetooth 2.0 + EDR;
 WLAN: 802.11b/g WPA2;
 WWAN: Quad-band GSM GPRS/EDGE

* To ensure best performance when temperatures are below -4 °F (-20 °C), be sure battery is inserted in the device only when in use. When device is not in use at these temperatures, keep batteries in a pocket or stored in a warmer area.

CERTIFICATIONS: FCC, CE/R & TTE, IC (Canada), C-Tick, RoHS Compliant, PTCRB, GCF Compliant, AT&T network compatible, Section 508 compliant, MIL-STD-461E RE102, MIL-STD-461E RS103

NOMAD CONFIGURATIONS									
	Flash	Keypad	Card slots	BT	GPS	802.11g	WWAN	Camera	Laser scanner
800B	512 MB	PDA/Num	SD/CF	x					
800L	1 GB	PDA/Num	SD/CF	x	x	x			
800LD	1 GB	Numeric	SD/USB	x	x	x			
800LC	1 GB	PDA/Num	SD	x	x	x		x	
800LE	1 GB	Numeric	SD	x	x	x		x	x
800X	2 GB	Numeric	SD/CF	x	x	x	x		
800XC	2 GB	Numeric	SD	x	x	x	x	x	
800XE	2 GB	Numeric	SD	x	x	x	x	x	x

Specifications subject to change without notice.

© 2008, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited registered in the United States and in other countries. Nomad is a trademark of Tripod Data Systems. Windows and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. All other brand names and trademarks are property of their owners. PN N2022490-030D (11/08)



YOUR LOCAL TRIMBLE DEALER

Trimble Navigation Limited
 P.O. Box 947
 Corvallis, OR 97339
 Phone 541-750-9200

Tripod Data Systems
 Authorized Trimble Distributor



www.trimble.com